



ER 307Si

Stainless Steel WIRE/GTAW



Standards

EN/ISO-Standard - 14343-A

EN/ISO-Classification - W 18 8 Mn

AWS-Standard - A5.9

AWS-Classification - ER 307Si

Features and Applications

- Austenitic stainless steel wire with a significant amount of manganese, making the all weld metal in most cases fully austenitic.
- High mechanical strength and excellent crack resistance.
- Increased silicon content promotes weld pool fluidity to give a smooth deposit appearance.
- Ideal for dissimilar welding between steel and stainless steel, armour plate and exhaust systems etc.
- Suitable for depositing stress relaxing buffer layers on crack sensitive base metals including hardfacing.
- Typically used on applications subject to atmospheric and corrosive media's.
- **Test Certificates can be found online @wilkinsonstar247.com**



Approvals

CE, UKCA

Typical Base Materials

Armour plate, exhaust systems (type 409, 304), high Manganese austenitic steel, difficult to weld steels such as 42CrMo4, C45, 42MnV7, tool steels, 1.3401, X120Mn12 etc.*

* Illustrative, not exhaustive list

Welding Positions

EN ISO 6947 - PA, PB, PC, PD, PE, PF

Shielding Gases

EN ISO 14175 - TIG: I1 (Argon)

Polarity

DC (-)

Mechanical Properties

Tensile Strength (N/mm ²)	Yield Strength (N/mm ²)	Elongation (%)	Impact Strength (J)
≥500	≥350	≥25	≥50

Mechanical properties are approximate and may vary based on the heat, shielding gas, welding parameters and other factors.

Chemical Composition % (Typical)

C %	Mn %	Si %	S %	P %	Ni %	Cr %	Mo %	Cu %
0.045	6.06	0.82	0.005	0.029	8.02	18.35	0.05	0.030

Packaging Data

Part No.	Diameter Ø (mm)	Package Length (mm)	Package Weight (Kg)	Package Type
6011100113	1.60	1000	5	Plastic Tube
6011100316	2.40	1000	5	Plastic Tube
6011100317	3.20	1000	5	Plastic Tube

Other diameters available on request

Liability: Whilst all reasonable efforts have been made to ensure the accuracy of the information contained, this information is subject to change without notice and can be only considered as suitable for general guidance.